



SIZE^(*)

| | | |
|--------|-----|----|
| HEIGHT | 199 | cm |
| WIDTH | 110 | cm |
| DEPTH | 68 | cm |
| WEIGHT | 400 | kg |

| | | |
|-----------------------------|----|--|
| SHELVES | 6 | <ul style="list-style-type: none"> • Can be increased up to 8 |
| CHANNELS | 42 | <ul style="list-style-type: none"> • Variable width pushers • Can be increased up to 60 |
| MATERIAL | | <ul style="list-style-type: none"> • Metal and SS • Electro plated treatment • Epoxy powder painted base, external polyester coating |
| LIGHTING | | <ul style="list-style-type: none"> • LED • IP67 Dissipated LED tubes • High brightness parallel diode with regulator |
| DISPLAY | | <ul style="list-style-type: none"> • 21.5" High brightness display (500 nits) FULL HD IPS LED • Vandal-proof touch capacitive screen IP59 |
| PC | | <ul style="list-style-type: none"> • Chipset Intel I5 FANLESS 4GB RAM SSD 120GB • 2 LAN 8 USB 4 RS232 • Windows |
| AIR CONDITIONER | | <ul style="list-style-type: none"> • Fridge composed by condensing unit and evaporator • Refrigerating Eco gas R314 • Minimum Temperature 20° |
| INCLUDED ACCESSORIES | | <ul style="list-style-type: none"> • Receipt printer for non delivery • Banknote reader • 5 pipes Self-recharging coin changer |
| OPTIONAL | | <ul style="list-style-type: none"> • Elegance Kit • 1200 nits TFT 21.5" • POS Device for electronic payment • Banknote reader giving change in banknotes (SPO) • Elevator • Dissuasion alarm with Siren • Rear Loading • Airflow conveyor towards outside • Robot connection Kit and pick-up drawer |
| POWER SUPPLY | | <ul style="list-style-type: none"> • 220-240VAC 50Hz (100-130VAC 60HZ optional) |
| POWER CONSUMPTION | | <ul style="list-style-type: none"> • Standby 80W + 800W in case of Fridge operation |

^(*)Reduced format available